

CA-GRL14UT

REAR METAL MESH SPEAKER GRILLES DESIGNED AND ENGINEERED
FOR 2014-UP HARLEY-DAVIDSON® ULTRA MOTORCYCLES

INSTRUCTION MANUAL

JVCKENWOOD Corporation

Important Notes

©2023 JVCKENWOOD Corporation. All Rights Reserved. KENWOOD® and eXcelon® are registered trademarks of JVCKENWOOD Corporation. Harley-Davidson®, Electra Glide®, Road Glide®, Street Glide®, Ultra Classic®, Tri Glide®, CVO™, Screamin Eagle® and Tour-Pak® are trademarks or registered trademarks of Harley-Davidson, Inc. and/or its affiliates and if used or implied are for reference only. There is no affiliation between Harley-Davidson, Inc. and/or its affiliates and JVCKENWOOD Corporation and/or its affiliates. All other trademarks are the property of their respective owners. Specifications subject to change without notice.

Take the time to read through this instruction manual.

Familiarity with installation and operation procedures will help you obtain the best performance from your new product.

Rear Metal Mesh Speaker Grilles Installation Instructions

NOTE: KENWOOD CA-GRL14UT grilles fit 2014+ factory rear speaker pods, the KENWOOD CA-POD14AC and CA-POD14LC, and can also be used if installing speakers in factory lower speaker adaptors for air-cooled bikes.

■ Installation procedure

1. Ensure your ignition switch stays in the "OFF" position.
2. Remove the factory rear speaker grilles by unscrewing the 4 "Torx" screws on the front of the grilles. With all 4 screws removed, the factory grilles will now come off the factory rear speaker "pod".
3. Set the new grilles in place, and using the factory screws removed earlier, secure the grille to the "pod" so the screws also go through the mounting holes in the speakers.

NOTE: The factory rubber "nutserts" on the rear pod side can be finicky. It's a good idea to get all 4 grille screws "started" and then get each one snug. Gradually tighten each one down making sure all 4 screws holding the grille down are secure.

NOTE: You can customize these grilles by carefully "breaking" the adhesive that holds the trim and mesh together on the back side of the grille. The trim is easily painted, and the metal mesh is thick enough that it should not warp during powder coating, polishing, chroming, or other similar processing.

For updated information (the latest Instruction Manual, etc.), please visit the following website:

https://manual.kenwood.com/en_contents/search/

