

CA-GRL98SG

FAIRING METAL MESH SPEAKER GRILLES DESIGNED AND ENGINEERED FOR 1996-2013 HARLEY-DAVIDSON® FLH MODEL MOTORCYCLES

INSTRUCTION MANUAL

JVCKENWOOD Corporation

Important Notes

©2023 JVCKENWOOD Corporation. All Rights Reserved. KENWOOD® and eXcelon® are registered trademarks of JVCKENWOOD Corporation. Harley-Davidson®, Electra Glide®, Road Glide®, Street Glide®, Ultra Classic®, Tri Glide®, CVO™, Screamin Eagle® and Tour-Pak® are trademarks or registered trademarks of Harley-Davidson, Inc. and/or its affiliates and if used or implied are for reference only. There is no affiliation between Harley-Davidson, Inc. and/or its affiliates and JVCKENWOOD Corporation and/or its affiliates. All other trademarks are the property of their respective owners. Specifications subject to change without notice.

Take the time to read through this instruction manual.

Familiarity with installation and operation procedures will help you obtain the best performance from your new product.

Fairing Metal Mesh Speaker Grilles Installation Instructions

NOTE: The mesh parts in this kit are designed to replace the front speaker grille cloth on 1996-2013 HD Street Glides, Ultras, Classics, and Standards.

■ Installation procedure

1. Remove your outer fairing.

NOTE: A towel or something similar is suggested to be placed over your front fender to help in preventing dings or scratches during installation.

2. Remove the speaker/grille assembly from the bike.

NOTE: The factory grille cloth is glued to a plastic mesh, and together, is two-way taped to the main body of the grille assembly. You can usually peel away the mesh from the body of the grille by hand. With the factory grille cloth/mesh off, you should see the exposed two-way tape used to hold the factory mesh on the main grille body. In most cases, the factory two-way tape will hold the new mesh in place, but the new two-way tape is supplied in the box if you need it (most adhesives work best at room temperature or higher).

3. Take a moment and ensure the new mesh is oriented so everything lines up properly and then re-install the speaker/grille assembly into the fairing.

NOTE: For custom applications, the metal mesh is thick enough that it should not warp during powder coating, polishing, chroming, or other similar processing.

For updated information (the latest Instruction Manual, etc.), please visit the following website:

https://manual.kenwood.com/en_contents/search/

