

elipson | Performance P300

STEREO PREAMPLIFIER



The stereo preamplifier from Elipson's PERFORMANCE range is the perfect choice for discerning audiophiles seeking exceptional sound quality. With its digital inputs including Bluetooth V5.1 APTX-HD, USB, Optical and Coaxial S/PDIF, as well as LAN, WIFI and Bluetooth streaming (Airplay2, Chromecast, UpNp, DLNA) via the Elipson app, this preamplifier offers extended connectivity for enjoying all possible audio sources.

The RCA asymmetrical and XLR symmetrical outputs ensure compatibility with a wide range of amplifiers, including the A300 power amplifier from Elipson's PERFORMANCE range. The Sub output (fc 400 Hz - slope 18 dB/oct) allows for connecting a subwoofer for an even more immersive sound experience.

This preamplifier is ideal for audiophiles seeking the perfect companion for Elipson's A300 amplifier from the PERFORMANCE range.



TECHNICAL

Type

Stereo preamplifier

Technology

ESS Sabre + Class D with integrated PFC

Nominal power Wrms into 4 & 8 Ω

2 x 130 W RMS

Frequency response

20 Hz - 50 kHz

Signal noise ratio

112 dBA

Analogue Inputs

Line In 1 and 2 - RCA

Numerical inputs

Bluetooth V5.1 APTX - HD – USB – Optical and Coaxial S/PDIF

Streamer

LAN – WIFI – Bluetooth (Airplay2, Chromecast, UpNp, DLNA) ELIPSON App

Outputs

RCA, Balanced XLR & Sub pre out (Cut-off frequency 400 Hz - slope 18 dB/oct)

Supported sample rate

Hi-Res : 24 Bit - 192 kHz

Headphone output

Jack 6.35 mm

Standby mode

Auto : Wake up / Off

Remote control

IR- multi functions

Main Power

100 - 240 V 50 / 60 Hz

Power consumption

< 0,5 W standby (EuP 2013) / 0,24 W

FINISHES

Gun grey anodizing / Satin black top cover

NICE TO KNOW



Designed, engineered and made
in France

DIMENSIONS WEIGHT

Dimensions

W430 x D287 x H80 mm
(with feet and connectors)

Net weight

TBC

PACKAGING

Dimensions packaging

TBC

Gross weight

TBC