

D.

DEFINITIVE TECHNOLOGY®



DEMAND SERIES | D5c

Center Channel Speaker

www.definitivetechology.com



DEMAND D5c

The Definitive Technology Demand D5c high-performance center channel speaker delivers full-range, room-filling sound and precise imaging in a modern, elegant styling. Ideal for complementing Demand Series tower speakers in a home cinema configuration.

SERIES FEATURES

2-Way Configuration

With dual 5.25" BDSS™ driver configuration and a 1" aluminum dome tweeter, dialogue from movies and music are perfectly reproduced. Voice matched to complement the Demand Series towers and bookshelf speakers and create an ideal home theater ensemble.

1" Aluminum Dome Tweeter with 20/20 Wave Alignment Lens™

Coupled with the 20/20 Wave Alignment Lens™, Definitive Technology 1" aluminum dome tweeters deliver a clear, precise high frequency response. The 20/20 Wave Alignment Lens smooths high frequencies off the tweeter for improved dispersion and a rich and balanced listening experience anywhere in your room.

BDSS™ (Balanced Double Surround System) Midrange

Patented Double Surround mid-range provides greater linear excursion and output that results in superior mid-range detail and punchier bass compared to drivers of similar size.

Extruded Aluminum Front Baffle

Clean, beautiful modern industrial design with an extruded aluminum front baffle bead-blasted finish that provides a timeless look and feel that fits any décor. Lightweight, durable and recyclable, aluminum is truly the metal of a modern lifestyle.

Acoustically Transparent Magnetic Grille

The included acoustically transparent magnetic speaker grilles provide natural, uncolored sound when placed on the speaker, and removes easily when you want to enjoy looking at them fully uncovered.

Designed in California

Our Design Studio is located in California, where technology and innovation meet entertainment. It goes beyond the idea of a centralized location — it's a cultural mindset that's the Definitive Technology wellspring for creativity and inspiration.

SPECIFICATIONS

Dimensions (L x W x H)	11.24 x 19.00 x 6.58 in 285.5 x 482.6 x 167.1mm
Product Weight	24 lbs / 10.9 kg
Tweeter	1" / 25mm
Midrange	5.25" / 130mm
-3dB LF (Hz)	42 Hz
-3dB HF (Hz)	22 kHz
2.83V/1m Sensitivity (dB SPL)	87 dB
Nominal Impedance	4 ohms
Tweeter/Midrange XO Point (Hz)	2.9 kHz
Midrange/Woofers XO Point (Hz)	280 Hz
Minimum Power	40 watts
Maximum Power	300 watts